

ProClean Non-Reflective Matt

Formulated for the professional painter and is known throughout the industry for its trusted formula and whiteness

PRODUCT DESCRIPTION

Fleetwood Pro-Clean Non-Reflective Matt offers an extremely low reflective matt finish which alleviates visual imperfections and eliminates flashing. A dead flat matt emulsion, it has been formulated to be anti-flashing and to provide a non-reflective finish at all angles, perfect for ceilings. It has excellent touching-up properties, providing near invisible touch-up for areas in critical lighting. Its water permeable properties make it ideal for period buildings.

USES

- Internal finish for all types of interior walls and ceilings.
- Perfect for bare and previously painted including plaster, plasterboard, concrete, ceiling tiles, wallcoverings etc.
- Ideal where the surface and site conditions, with critical lighting could combine to be a potential issue.
- Class 1 scrub rating

CHARACTERISTICS / ADVANTAGES

- Excellent durability
- LRV Rating 90
- Class 1 scrubability EN13300 & ISO11998
- Quick drying
- Low VOC and odour
- Easy application by spray
- Excellent coverage and opacity
- Flat matt finish
- Water vapour permeable

APPROVALS / STANDARDS

VOC Content

- 2004/42/EC EU limit value for this product (cat.A/a WB): 30g/l (2010) This product contains max. 2.0 g/l VOC.

Water Vapour Permeability


- Water Vapour Permeability (BS EN ISO 7783)
- Class: V2 Medium SD Value = 0.49, V = 48g/m²

Water Absorption Co-efficient

- Water permeability EN 1062-3:2018(E)
- W kg/(m²h) W = High > 0.5

Quality Control

- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



NBS



NBS Chorus



Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: technical@fleetwood.ie Tel: +353 49 854 7209 (weekdays 9am-5pm)

Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



Colour

Colours Brilliant White & Tinted To Pastal Colours

Colour Collections Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



SHERWIN
WILLIAMS

PANTONE®



Specification

Composition	Water-based acrylic.
Number of Components	1
Recommended number of coats	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
Usage Interior/Exterior	Interior.
Application Tools	Brush, roller or spray.
Coverage	Approx. 14m ² per litre, per coat.
Overcoat Times	Recoat after 4 hours.
Curing Time	Touch dry in 30 minutes, fully cured after 7 to 10 days.
Suitable For	New or previously painted drywall, plaster, cement, concrete and other paintable surfaces.
Min. application temperature	4°C
Pack Size	5L, 10L
Shelf Life	3 years in unopened container.
Storage	Do not allow to freeze.
Cleaning Tools	Wash application tools in warm, soapy water immediately after use. .
Principle Limitations Please contact us regarding applications not described here	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.

Product Information

Colour Range:	Brilliant White
LRV Range:	90
VOC Content:	Contains max VOC; 2.0 g/l Conforms to EU 2010 Directive (Cat A/a) 30g/l
Composition:	Pigment: Lightfast Pigments Binder: Styrene arylc copolymer emulsion. Solvent: Water
Solids:	Volume Solids 347.5 % (+/- 2%) Weight Solids 55.5 % (+/- 2%) Specific Gravity 1.41 g/l (+/- 0.15) Gloss at 85° < 1.2 pH -Value > 8.2

Technical Data Sheet

Pro-Clean Non-Reflective Matt
F-313
February 2025
Issue 3

Product Information Cont.

Surface Preparation:	Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material. Treat powdery surfaces with Fleetwood Masonry Primer. Surfaces to be painted must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation or pre-1960s paint surfaces over wood and metal as they may contain harmful lead.
Application:	Brush, roller, spray & airless spray. As with other water-based paints, do not apply in temperatures below 5°C
Spreading Rate:	As a guide, a coverage rate of up to 14m ² per litre, per coat. can be achieved under normal conditions
Reduction:	Reduce by up to 20% as required by application and or equipment. When applying over previously painted matt surfaces, it is good practice to apply the 1st coat at 105 dilutions.
Spray Recommendations:	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/in ²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60
Drying Time:	Touch Dry: 2 hours Recoat: 2 – 4 hours This is dependent upon temperature and humidity. Darker colours may take longer 26°C to 50% RH @ 100 µm
Cleaning Up:	Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.
Tint Instructions:	Tint only with Fleetwood Tinting systems
Previously Painted Surfaces:	Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.
Precautions:	If in sound condition, clean the surface of all foreign material. Glossy surfaces must be rubbed down to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new. Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport all containers in upright position. Select sensible working clothes that cover as much of the body as possible. Always wear gloves and use eye protection. Do not touch your mouth or eyes with your gloves.

Limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application on +353 49 854 7209 technical@fleetwood.ie

Solids:

Technical Data Sheet
Pro-Clean Non-Reflective Matt
F-313

February 2025
Issue 1